

IN THE SPECIFICATION

On page 4, lines 3 substitute the following:

Figure 10 is a larger-scale view of the detail X [[10]] of Figure 6.

Please amend the paragraph beginning on page 4, line 11 as follows:

At its rear portion, the rear portion ~~roof element~~ 4 supports brackets 6, on each of which a guide finger 7 is mounted. The guide finger co-operates with a runner 8 secured to the structure of the vehicle.

Please amend the paragraph beginning on page 4, line 15 as follows:

In addition, the rear portion ~~roof element~~ 4 is actuated by an actuator 9 via an arm 10. The arm 10 has one of its ends hinged to the structure of the vehicle about a transverse axis 11, and its other end is provided with a finger 12 engaged in a runner 13 that is secured to the rear element 4.

Please amend the paragraph beginning on page 4, line 20 as follows:

The front portion ~~roof element~~ 5 is mounted to slide via its extension 14 in a runner 15.

Please amend the paragraph beginning on page 5, line 7 as follows:

As shown in Figure 2, the front roof element 5 is driven on the runner 15 by means of a motor 21 that is secured to the element 5. To this end, a finger 22 guides the element 5 in the runner 15, and a rack system 23 that is secured to the finger ~~wheel~~ 22 and that is driven by the motor 21 makes it possible to actuate the element 5 in the runner 15.

Please amend the paragraph beginning on page 5, line 20 as follows:

The arm 10 is also provided with a member ~~finger~~ 30 that is suitable for coming into abutment on a lug 31 that is secured to or integral with the slide 15 (Figure 7).

IN THE DRAWINGS

Substitute the enclosed figures 1, 6 and 9 for the previously submitted figures.